



Manu Data

Sliding Door 2¼ Panel – Aluminum Clad

Frame:

- Pine, red grandis or mahogany
- Aluminium clad, extruded 0.060", 1.5mm thick
- Thickness 1 ¼" (32mm)
- Depth 7 9/16" (192mm)
- Sill: Fiberglass

Panel:

- Pine, red grandis or mahogany
- Exterior clad, extruded aluminium 0.100 (2.5mm)
- Thickness 2 ¼" (57mm)
- Colonial or contemporary
- Stiles and top rail width: 5" or 3 5/8"
- Bottom rail 9", 5" or 3 5/8"
- Choice of flat or raised panels

Interior finish:

- Natural, primed, first coat, Lepage stain or paint over 50 colors

Exterior finish:

- Lepage paint over 50 colors

Hardware:

- Satin chrome, satin nickel, antique nickel, polish brass, antique brass, oil rubbed bronze or black
- Tandem rollers adjustable

Weather-strip

- Q-Lon Schlegel

Insulated glass tempered:

- Double glaze ¾" (19 mm)
- Triple glaze 1 ¼" (32mm)
- "Technoform" spacer, bronze, white, black or grey.
- Argon

Glass available:

- Clear, grey, bronze, pinhead, glue-chip
- Low-e: Energy advantage, 272, 366, 189
- Laminated

Sliding Screen:

- Mesh: invisible fiberglass, grey or black aluminium
- WS-07 white aluminum sliding screen or Lepage paint over 50 colors

Grilles:

- Internal georgian $\frac{3}{4}$ ", 1" or 1 $\frac{3}{4}$ "
- Internal flat $\frac{5}{16}$ ", $\frac{5}{8}$ ", $\frac{3}{4}$ " or 1"
- Internal tubular: white, brass or pewter

Simulated Divided Lites (SDL):

- $\frac{5}{8}$ ", $\frac{7}{8}$ ", 1 $\frac{1}{4}$ " or 1 $\frac{3}{4}$ "
- Spacer bars bronze, grey, white or black

True Divided Lites (TDL):

- TDL 5" or 3 $\frac{5}{8}$ "

Casing:

- 908
- 2 $\frac{3}{4}$ " Flat casing
- 3 $\frac{1}{2}$ " Flat casing
- 3 $\frac{15}{16}$ " Backbend (D-090)
- Nailing fin

Interior Jamb Extension:

- Finish and wood species same as interior frame 1/8" min and 6" max

Minimums and Maximums for 2 panels configuration:

Minimum width:	60"	Maximum width:	108"
Minimum height:	48"	Maximum height:	108"

Maximum 40 square feet (IG)

For more information, please visit our web site at www.lepagemillwork.com