

FRENCH INSWING CASEMENT

WFC11

Transom

						
	1005	1205	1405	1805	2205	2605
						
	1009	1209	1409	1809	2209	2609
R.O. (mm)	18 3/8" (466)	20 1/4" (514)	22 3/4" (565)	26 3/4" (667)	30 3/8" (765)	34 1/8" (866)
F.S. (mm)	17 3/8" (441)	19 3/4" (489)	21 3/4" (540)	25 3/4" (641)	29 3/8" (740)	33 3/8" (841)
V.G. (mm)	9 1/4" (236)	11 3/8" (284)	13 3/8" (335)	17 3/8" (436)	21" (535)	25" (636)
						
	1013	1213	1413	1813	2213	2613
						
	1017	1217	1417	1817	2217	2617
						
	1021	1221	1421	1821	2221	2621
						
	1025	1225	1425	1825	2225	2625
						
	1029	1229	1429	1829	2229	2629
						
	1035	1235	1435	1835	2235	2635
						
	1041	1241	1441	1841	2241	2641
						
	1048	1248	1448	1848	2248	2648
						
	1053	1253	1453	1853	2253	2653
						
	1059	1259	1459	1859	2259	2659
						
	1065	1265	1465	1865	2265	2665

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative. Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all unit. Units with 14 1/8" (359) and 18 3/8" (460) and heights are shown stationary as standard transoms.

FRENCH INSWING CASEMENT

WFC21

Transom						
	18 5/8" (473)	14 5/8" (372)				
	18 1/8" (460)	14 1/8" (359)				
	8 3/8" (272)	4 3/8" (111)				
						
						
R.O. (mm)	33 3/4" (845)	37 1/4" (946)	41 1/8" (1045)	49" (1245)	56 7/8" (1445)	64 3/4" (1645)
F.S. (mm)	32 1/4" (819)	36 1/4" (921)	40 1/8" (1019)	48" (1219)	55 5/8" (1419)	63 3/4" (1619)
V.G. (mm)	9 3/8" (238)	11 3/8" (289)	13 3/8" (338)	17 1/4" (438)	21 1/4" (538)	25 3/8" (638)
						
						
						
						
						
						
						
						
						
						
						
R.O. (mm)	74 3/4" (1899)	68 3/4" (1747)	62 7/8" (1597)	57" (1448)	50 1/8" (1273)	44 1/4" (1124)
F.S. (mm)	74 1/4" (1886)	68 1/4" (1734)	62 3/8" (1584)	56 1/2" (1435)	49 5/8" (1260)	43 3/4" (1111)
V.G. (mm)	64 1/2" (1638)	58 1/2" (1486)	52 5/8" (1336)	46 3/4" (1187)	39 7/8" (1012)	34" (863)

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative. Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all unit. Units with 14 5/8" (359) and 18 5/8" (460) and heights are shown stationary as standard transoms.

WFC31

Page 10 of 10






















































Transom

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative. Lite patterns shown are 7/8" (22) SDL. Lite patterns for 9/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all unit Units with 14 1/2" (359) and 18 1/2" (460) and heights are shown stationary as standard transoms.

FRENCH INSWING CASEMENT

WFC41 (2 openings)

Transom					
	 1205	 1405	 1805	 2205	 2605
	 1209	 1409	 1809	 2209	 2609
R.O. (mm)	73 1/4" (1861)	81 1/8" (2061)	96 7/8" (2461)	112 5/8" (2861)	128 3/8" (3261)
F.S. (mm)	72 3/4" (1835)	80 5/8" (2035)	95 7/8" (2435)	111 5/8" (2835)	127 3/8" (3235)
V.G. (mm)	11 1/4" (287)	13 1/4" (337)	17 1/4" (437)	21 1/8" (537)	25 1/8" (637)
R.O. (mm)	 1213	 1413	 1813	 2213	 2613
	 1217	 1417	 1817	 2217	 2617
	 1221	 1421	 1821	 2221	 2621
	 1225	 1425	 1825	 2225	 2625
	 1229	 1429	 1829	 2229	 2629
	 1235	 1435	 1835	 2235	 2635
	 1241	 1441	 1841	 2241	 2641
	 1248	 1448	 1848	 2248	 2648
	 1253	 1453	 1853	 2253	 2653
	 1259	 1459	 1859	 2259	 2659
	 1265	 1465	 1865	 2265	 2665
	 1271	 1471	 1871	 2271	 2671
	 1277	 1477	 1877	 2277	 2677
	 1283	 1483	 1883	 2283	 2683
	 1289	 1489	 1889	 2289	 2689
	 1295	 1495	 1895	 2295	 2695
	 1301	 1501	 1901	 2301	 2701
	 1307	 1507	 1907	 2307	 2707
	 1313	 1513	 1913	 2313	 2713
	 1319	 1519	 1919	 2319	 2719
	 1325	 1525	 1925	 2325	 2725
	 1331	 1531	 1931	 2331	 2731
	 1337	 1537	 1937	 2337	 2737
	 1343	 1543	 1943	 2343	 2743
	 1349	 1549	 1949	 2349	 2749
	 1355	 1555	 1955	 2355	 2755
	 1361	 1561	 1961	 2361	 2761
	 1367	 1567	 1967	 2367	 2767
	 1373	 1573	 1973	 2373	 2773
	 1379	 1579	 1979	 2379	 2779
	 1385	 1585	 1985	 2385	 2785
	 1391	 1591	 1991	 2391	 2791
	 1397	 1597	 1997	 2397	 2797
	 1403	 1603	 2003	 2403	 2803
	 1409	 1609	 2009	 2409	 2809
	 1415	 1615	 2015	 2415	 2815
	 1421	 1621	 2021	 2421	 2821
	 1427	 1627	 2027	 2427	 2827
	 1433	 1633	 2033	 2433	 2833
	 1439	 1639	 2039	 2439	 2839
	 1445	 1645	 2045	 2445	 2845
	 1451	 1651	 2051	 2451	 2851
	 1457	 1657	 2057	 2457	 2857
	 1463	 1663	 2063	 2463	 2863
	 1469	 1669	 2069	 2469	 2869
	 1475	 1675	 2075	 2475	 2875
	 1481	 1681	 2081	 2481	 2881
	 1487	 1687	 2087	 2487	 2887
	 1493	 1693	 2093	 2493	 2893
	 1499	 1699	 2099	 2499	 2899
	 1505	 1705	 2105	 2505	

FRENCH INSWING CASEMENT

WFC41 (4 openings)

Transom					
					
	1205	1405	1805	2205	2605
					
	1209	1409	1809	2209	2609
R.O. (mm)	72" (1829)	79 7/8" (2029)	95 5/8" (2429)	111 3/8" (2829)	127 1/8" (3229)
F.S. (mm)	71" (1803)	78 7/8" (2003)	94 5/8" (2403)	110 3/8" (2804)	126 1/8" (3204)
V.G. (mm)	11 3/8" (288)	13 1/4" (338)	17 1/4" (438)	21 1/8" (538)	25 1/8" (638)
R.O. (mm)	57" (1448)	62 7/8" (1597)	68 3/4" (1747)	74 3/4" (1899)	80 1/2" (2047)
	58 1/2" (1486)	63 7/8" (1636)	69 3/4" (1786)	75 3/4" (1938)	81 1/2" (2086)
	59 1/2" (1524)	64 7/8" (1674)	70 3/4" (1824)	76 3/4" (1976)	82 1/2" (2124)
	60 1/2" (1562)	65 7/8" (1712)	71 3/4" (1862)	77 3/4" (2014)	83 1/2" (2162)
	61 1/2" (1600)	66 7/8" (1750)	72 3/4" (1900)	78 3/4" (2052)	84 1/2" (2200)
	62 1/2" (1638)	67 7/8" (1788)	73 3/4" (1938)	79 3/4" (2090)	85 1/2" (2238)
	63 1/2" (1676)	68 7/8" (1826)	74 3/4" (1976)	80 3/4" (2128)	86 1/2" (2276)
	64 1/2" (1714)	69 7/8" (1864)	75 3/4" (2014)	81 3/4" (2166)	87 1/2" (2314)
	65 1/2" (1752)	70 7/8" (1902)	76 3/4" (2052)	82 3/4" (2204)	88 1/2" (2352)
	66 1/2" (1790)	71 7/8" (1940)	77 3/4" (2090)	83 3/4" (2242)	89 1/2" (2390)
	67 1/2" (1828)	72 7/8" (1978)	78 3/4" (2128)	84 3/4" (2280)	90 1/2" (2428)
	68 1/2" (1866)	73 7/8" (2016)	79 3/4" (2166)	85 3/4" (2318)	91 1/2" (2466)
	69 1/2" (1904)	74 7/8" (2054)	80 3/4" (2204)	86 3/4" (2356)	92 1/2" (2504)
	70 1/2" (1942)	75 7/8" (2092)	81 3/4" (2242)	87 3/4" (2394)	93 1/2" (2542)
	71 1/2" (1980)	76 7/8" (2130)	82 3/4" (2280)	88 3/4" (2432)	94 1/2" (2580)
	72 1/2" (2018)	77 7/8" (2168)	83 3/4" (2318)	89 3/4" (2470)	95 1/2" (2618)
F.S. (mm)	56 1/2" (1435)	61 7/8" (1584)	67 3/4" (1734)	73 3/4" (1886)	79 1/2" (2037)
	57 1/2" (1473)	62 7/8" (1622)	68 3/4" (1772)	74 3/4" (1924)	80 1/2" (2075)
	58 1/2" (1511)	63 7/8" (1660)	69 3/4" (1810)	75 3/4" (1962)	81 1/2" (2113)
	59 1/2" (1549)	64 7/8" (1698)	70 3/4" (1848)	76 3/4" (2000)	82 1/2" (2151)
	60 1/2" (1587)	65 7/8" (1736)	71 3/4" (1886)	77 3/4" (2038)	83 1/2" (2189)
	61 1/2" (1625)	66 7/8" (1774)	72 3/4" (1924)	78 3/4" (2076)	84 1/2" (2227)
	62 1/2" (1663)	67 7/8" (1812)	73 3/4" (1962)	79 3/4" (2114)	85 1/2" (2265)
	63 1/2" (1701)	68 7/8" (1850)	74 3/4" (2000)	80 3/4" (2152)	86 1/2" (2303)
	64 1/2" (1739)	69 7/8" (1888)	75 3/4" (2038)	81 3/4" (2190)	87 1/2" (2341)
	65 1/2" (1777)	70 7/8" (1926)	76 3/4" (2076)	82 3/4" (2228)	88 1/2" (2379)
	66 1/2" (1815)	71 7/8" (1964)	77 3/4" (2114)	83 3/4" (2266)	89 1/2" (2417)
	67 1/2" (1853)	72 7/8" (2002)	78 3/4" (2152)	84 3/4" (2304)	90 1/2" (2455)
	68 1/2" (1891)	73 7/8" (2040)	79 3/4" (2190)	85 3/4" (2342)	91 1/2" (2493)
	69 1/2" (1929)	74 7/8" (2078)	80 3/4" (2228)	86 3/4" (2380)	92 1/2" (2531)
	70 1/2" (1967)	75 7/8" (2116)	81 3/4" (2266)	87 3/4" (2418)	93 1/2" (2569)
	71 1/2" (2005)	76 7/8" (2154)	82 3/4" (2304)	88 3/4" (2456)	94 1/2" (2607)
V.G. (mm)	10 1/8" (259)	12 1/4" (313)	16 1/4" (413)	20 1/8" (513)	24 1/8" (613)
	10 3/8" (267)	12 3/4" (321)	16 3/4" (421)	20 3/8" (521)	24 3/8" (621)
	10 5/8" (275)	13 1/4" (329)	17 1/4" (429)	21 1/8" (529)	25 1/8" (629)
	10 7/8" (283)	13 3/4" (337)	17 3/4" (437)	21 3/8" (537)	25 3/8" (637)
	11 1/8" (291)	14 1/4" (345)	18 1/4" (445)	22 1/8" (545)	26 1/8" (645)
	11 3/8" (299)	14 3/4" (353)	18 3/4" (453)	22 3/8" (553)	26 3/8" (653)
	11 5/8" (307)	15 1/4" (361)	19 1/4" (461)	23 1/8" (561)	27 1/8" (661)
	11 7/8" (315)	15 3/4" (369)	19 3/4" (469)	23 3/8" (569)	27 3/8" (669)
	12 1/8" (323)	16 1/4" (377)	20 1/4" (477)	24 1/8" (577)	28 1/8" (677)
	12 3/8" (331)	16 3/4" (385)	20 3/4" (485)	24 3/8" (585)	28 3/8" (685)
	12 5/8" (339)	17 1/4" (393)	21 1/4" (493)	25 1/8" (593)	29 1/8" (693)
	12 7/8" (347)	17 3/4" (401)	21 3/4" (501)	25 3/8" (601)	29 3/8" (701)
	13 1/8" (355)	18 1/4" (409)	22 1/4" (509)	26 1/8" (609)	30 1/8" (709)
	13 3/8" (363)	18 3/4" (417)	22 3/4" (517)	26 3/8" (617)	30 3/8" (717)
	13 5/8" (371)	19 1/4" (425)	23 1/4" (525)	27 1/8" (625)	31 1/8" (725)
	13 7/8" (379)	19 3/4" (433)	23 3/4" (533)	27 3/8" (633)	31 3/8" (733)






















* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative. Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all unit. Units with 14 1/8" (359) and 18 1/8" (460) and heights are shown stationary as standard transoms.

FRENCH INSWING CASEMENT

WFC51

Transom	18 5/8" (473)	14 5/8" (372)					
	18 1/8" (460)	14 1/8" (359)					
	8 3/8" (272)	4 3/8" (111)					
							
							
R.O. (mm)	90" (2286)	99 3/4" (2534)	119 1/2" (3035)	139 1/8" (3534)	158 7/8" (4035)		
F.S. (mm)	89" (2261)	98 3/4" (2508)	118 1/2" (3010)	138 1/8" (3508)	157 7/8" (4010)		
V.G. (mm)	11 1/4" (287)	13 1/4" (337)	17 1/4" (437)	21 1/8" (537)	25 1/8" (637)		
							
							
							
							
							
							
							
							
							
							
							

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative. Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all unit. Units with 14 1/8" (359) and 18 1/8" (460) and heights are shown stationary as standard transoms.




































































WFC2L

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative.

Lite patterns shown are $\frac{3}{8}$ " (22) SDL. Lite patterns for $\frac{5}{8}$ " (16) SDL, $1\frac{1}{4}$ " (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all unit Lite with $1\frac{1}{2}$ " (359) and $18\frac{1}{2}$ " (460) and heights are shown stationarily as standard transoms. Some restriction concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.

FRENCH INSWING CASEMENT

WFC3L

R.O.: Rough Opening F.S.: Frame Size V.G.: Visible Glass		W.F.: Width of Flanker (comparable to the WFC-11 series) V.G.F.: Visible Glass of Flanker V.G.P.: Visible Glass of Picture Unit																			
		Transom																			
R.O. (mm)	F.S. (mm)	V.G. (mm)	74 3/4" (1899)	68 3/4" (1747)	62 7/8" (1597)	57" (1448)	50 1/8" (1273)	44 1/4" (1124)	38 1 1/4" (972)	34 3/8" (873)	30 3/2" (775)	26 1/2" (673)	22 1/2" (572)	18 5/8" (473)	14 5/8" (372)						
F.S. (mm)	V.G. (mm)	V.G.P. (mm)	74 1/4" (1886)	68 1/4" (1734)	62 3/8" (1584)	56 1/2" (1435)	49 5/8" (1260)	43 3/4" (1111)	37 3/4" (959)	33 7/8" (860)	30" (762)	25" (660)	22" (659)	18 1/8" (460)	14 3/8" (359)						
V.G. (mm)	V.G.P. (mm)	V.G.F. (mm)	64 1/2" (1638)	58 1/2" (1486)	52 5/8" (1336)	46 3/4" (1187)	39 7/8" (1012)	34" (863)	28" (711)	24 1/4" (612)	20 1/4" (514)	16 1/4" (412)	12 1/4" (311)	8 3/8" (272)	4 3/8" (111)						
																					
			3265	3465	4165	4565	4965	5665								3205	3405	4105	4505	4905	5605
																					
			3259	3459	4159	4559	4959	5659								3209	3409	4109	4509	4909	5609
																					
			3248	3448	4148	4548	4948	5648								3213	3413	4113	4513	4913	5613
																					
			3241	3441	4141	4541	4941	5641								3217	3417	4117	4517	4917	5617
																					
			3235	3435	4135	4535	4935	5635								3221	3421	4121	4521	4921	5621
																					
			3229	3429	4129	4529	4929	5629								3225	3425	4125	4525	4925	5625
																					
			3221	3421	4121	4521	4921	5621								3217	3417	4117	4517	4917	5617
																					
			3213	3413	4113	4513	4913	5613								3209	3409	4109	4509	4909	5609
																					
			3205	3405	4105	4505	4905	5605								3201	3401	4101	4501	4901	5601

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative.

Lite patterns shown are $\frac{7}{8}"$ (22) SDL. Lite patterns for $\frac{9}{16}"$ (16) SDL, $1\frac{1}{4}"$ (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all units. Units with $14\frac{1}{2}"$ (359) and $18\frac{1}{2}"$ (460) and heights are shown stationary as standard transoms. Some restriction concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.