

AWNING WINDOWS

A100-11

R.O. (mm)	25" (635)	29" (737)	33" (838)	37" (940)	41" (1041)	49" (1245)
F.S. (mm)	24" (610)	28" (711)	32" (813)	36" (914)	40" (1016)	48" (1219)
V.G. (mm)	17 1/2" (446)	21 1/2" (547)	25 1/2" (649)	29 1/2" (751)	33 1/2" (853)	41 1/2" (1055)
R.O. (mm)	36 1/2" (927)	40 1/2" (1029)	48 1/2" (1232)			
F.S. (mm)	36" (914)	40" (1016)	48" (1219)			
V.G. (mm)	29 1/2" (750)	33 1/2" (852)	41 1/2" (1055)			
						
						
						
						
						
						
						
						

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Awning windows do not meet Egress requirements.

Venting configurations shown in units of the first line and first column are applicable to all units.

AWNING WINDOWS

A100-12

R.O. (mm)	25" (635)	29" (737)	33" (838)	37" (940)	41" (1041)	49" (1245)
F.S. (mm)	24" (610)	28" (711)	32" (813)	36" (914)	40" (1016)	48" (1219)
V.G. (mm)	17 1/2" (446)	21 1/2" (547)	25 1/2" (649)	29 1/2" (751)	33 1/2" (852)	41 1/2" (1055)
R.O. (mm)	72 1/2" (1842)	48 1/2" (1232)	48 1/2" (1232)	40 1/2" (1029)	40 1/2" (1029)	40 1/2" (1029)
F.S. (mm)	72" (1829)	48" (1219)	48" (1219)	40" (1016)	40" (1016)	40" (1016)
V.G. (mm)	29 1/2" (749)	17 1/2" (444)	17 1/2" (444)	13 1/2" (342)	13 1/2" (342)	13 1/2" (342)
						
	1814	2214	2614	3014	3414	4214
						
	1818	2218	2618	3018	3418	4218
						
	1822	2222	2622	3022	3422	4222
						
	1826	2226	2626	3026	3426	4226
						
	1830	2230	2630	3030	3430	4230

A100-D

R.O. (mm)	78 3/8" (1991)	66 3/8" (1686)	54 3/8" (1381)	48 3/8" (1229)	48 3/8" (1229)	48 3/8" (1229)
F.S. (mm)	77 7/8" (1978)	65 7/8" (1674)	53 7/8" (1369)	47 7/8" (1217)	47 7/8" (1217)	47 7/8" (1217)
H.A. (mm)	28" (711)	24" (610)	20" (508)	18" (457)	18" (457)	18" (457)
V.G.A. (mm)	21 1/2" (547)	17 1/2" (446)	13 1/2" (344)	11 1/2" (293)	11 1/2" (293)	11 1/2" (293)
V.G.P. (mm)	43 1/4" (1100)	35 1/4" (896)	27 1/4" (693)	23 1/4" (592)	23 1/4" (592)	23 1/4" (592)
						
	1812	2212	2612	3012	3412	4212
						
	1814	2214	2614	3014	3414	4214
						
	1818	2218	2618	3018	3418	4218
						
	1822	2222	2622	3022	3422	4222

R.O.: Rough Opening
F.S.: Frame Size
H.A.: Height of Awning
V.G.: Visible Glass
V.G.A.: Visible Glass of Awning
V.G.P.: Visible Glass of Picture Unit

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative.













Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Awning windows do not meet Egress requirements.

Venting configurations shown in units of the first line and first column are applicable to all units.

Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq.ft.

AWNING WINDOWS

A100-21

R.O. (mm)	47 7/8" (1216)	55 7/8" (1419)	63 7/8" (1622)	71 7/8" (1826)	79 7/8" (2029)	95 7/8" (2435)
F.S. (mm)	46 7/8" (1191)	54 7/8" (1394)	62 7/8" (1597)	70 7/8" (1800)	78 7/8" (2003)	94 7/8" (2410)
V.G. (mm)	17 1/8" (435)	21 1/2" (546)	25 1/2" (648)	29 1/2" (749)	33 1/2" (851)	41 1/2" (1054)
18 1/2" (470)						
20 1/2" (521)						
24 1/2" (622)						
28 1/2" (724)						
32 1/2" (826)						
36 1/2" (927)						
40 1/2" (1029)						
48 1/2" (1232)						

R.O. (mm)

F.S. (mm)

V.G. (mm)

R.O.: Rough Opening

F.S.: Frame Size

V.G.: Visible Glass

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local Lepage representative.

Lite patterns shown are $\frac{7}{8}$ " (22) SDL. Lite patterns for $\frac{5}{8}$ " (16) SDL, $1\frac{1}{4}$ " (31) SDL and other grilles may vary.

Awning windows do not meet Egress requirements.

Venting configurations shown in units of the first line and first column are applicable to all units.

AWNING WINDOWS

A100-22

R.O. (mm)	47 7/8" (1216)	55 7/8" (1419)	63 7/8" (1622)	71 7/8" (1826)	79 7/8" (2029)	95 7/8" (2435)
F.S. (mm)	46 7/8" (1191)	54 7/8" (1394)	62 7/8" (1597)	70 7/8" (1800)	78 7/8" (2003)	94 7/8" (2410)
V.G. (mm)	17 1/8" (435)	21 1/2" (546)	25 1/2" (648)	29 1/2" (749)	33 1/2" (851)	41 1/2" (1054)
R.O. (mm)	72 1/2" (1842)	72" (1829)	72" (1829)	72" (1829)	72" (1829)	72" (1829)
F.S. (mm)	72" (1829)	72" (1829)	72" (1829)	72" (1829)	72" (1829)	72" (1829)
V.G. (mm)	29 1/2" (750)	29 1/2" (750)	29 1/2" (750)	29 1/2" (750)	29 1/2" (750)	29 1/2" (750)
	1814	2214	2614	3014	3414	4214
	1818	2218	2618	3018	3418	4218
	1822	2222	2622	3022	3422	4222
	1826	2226	2626	3026	3426	4226
	1830	2230	2630	3030	3430	4230

A100-2D

R.O. (mm)	78 3/8" (1991)	66 3/8" (1686)	54 3/8" (1381)	48 3/8" (1229)
F.S. (mm)	77 7/8" (1978)	65 7/8" (1674)	53 7/8" (1369)	47 7/8" (1217)
H.A. (mm)	28" (711)	24" (610)	20" (508)	18" (457)
V.G.A. (mm)	21 1/2" (548)	17 1/2" (446)	13 1/2" (344)	11 1/2" (293)
V.G.P. (mm)	43 3/8" (1101)	35 1/2" (898)	27 1/2" (693)	23 1/2" (592)
	1812	2212	2612	3012
	1814	2214	2614	3014
	1818	2218	2618	3018
	1822	2222	2622	3022
	3412	3414	3418	3422
	4212	4214	4218	4222

Grille configurations shown have been designed for grilles to align with bottom awnings, therefore lite cuts are NOT equal. Equal lite cuts are available on request but will NOT ALIGN with the grilles in the bottom sections.

R.O.: Rough Opening
F.S.: Frame Size
H.A.: Height of Awning
V.G.: Visible Glass
V.G.A.: Visible Glass of Awning
V.G.P.: Visible Glass of Picture Unit

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local Lepage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Awning windows do not meet Egress requirements.

Venting configurations shown in units of the first line and first column are applicable to all units.