

PUSH-OUT AWNING WINDOWS

POA100-11

R.O. (mm)	25" (635)	29" (737)	33" (838)	37" (940)	41" (1041)	49" (1245)
F.S. (mm)	24" (610)	28" (711)	32" (813)	36" (914)	40" (1016)	48" (1219)
V.G. (mm)	17 1/2" (446)	21 1/2" (547)	25 1/2" (649)	29 1/2" (751)	33 1/2" (853)	41 1/2" (1055)
R.O. (mm)	36 1/2" (927)	40 1/2" (1029)	48 1/2" (1232)			
F.S. (mm)	36" (914)	40" (1016)	48" (1219)			
V.G. (mm)	29 1/2" (750)	33 1/2" (852)	41 1/2" (1055)			
						
	1812	2212	2612	3012	3412	4212
						
	1814	2214	2614	3014	3414	4214
						
	1818	2218	2618	3018	3418	4218
						
	1822	2222	2622	3022	3422	4222
						
	1826	2226	2626	3026	3426	4226
						
	1830	2230	2630	3030	3430	4230
						
	1834	2234	2634	3034	3434	4234
						
	1842	2242	2642	3042	3442	4242

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Awning windows do not meet Egress requirements.

Venting configurations shown in units of the first line and first column are applicable to all units.

PUSH-OUT AWNING WINDOWS

POA100-12

R.O. (mm)	25" (635)	29" (737)	33" (838)	37" (940)	41" (1041)	49" (1245)
F.S. (mm)	24" (610)	28" (711)	32" (813)	36" (914)	40" (1016)	48" (1219)
V.G. (mm)	17 1/2" (446)	21 1/2" (547)	25 1/2" (649)	29 1/2" (751)	33 1/2" (852)	41 1/2" (1055)
R.O. (mm)	72 1/2" (1842)	48 1/2" (1232)	48 1/2" (1232)	48 1/2" (1232)	48 1/2" (1232)	48 1/2" (1232)
F.S. (mm)	72" (1829)	48" (1219)	48" (1219)	48" (1219)	48" (1219)	48" (1219)
V.G. (mm)	29 1/2" (749)	17 1/2" (444)	17 1/2" (444)	17 1/2" (444)	17 1/2" (444)	17 1/2" (444)
						
	1814	2214	2614	3014	3414	4214
						
	1818	2218	2618	3018	3418	4218
						
	1822	2222	2622	3022	3422	4222
						
	1826	2226	2626	3026	3426	4226
						
	1830	2230	2630	3030	3430	4230

POA100-D

R.O. (mm)	78 3/8" (1991)	66 3/8" (1686)	54 3/8" (1381)	48 3/8" (1229)
F.S. (mm)	77 7/8" (1978)	65 7/8" (1674)	53 7/8" (1369)	47 7/8" (1217)
H.A. (mm)	28" (711)	24" (610)	20" (508)	18" (457)
V.G.A. (mm)	21 1/2" (547)	17 1/2" (446)	13 1/2" (344)	11 1/2" (293)
V.G.P. (mm)	43 1/4" (1100)	35 1/4" (896)	27 1/4" (693)	23 1/4" (592)
				
	1812	2212	2612	3012
				
	1814	2214	2614	3014
				
	1818	2218	2618	3018
				
	1822	2222	2622	3022
				
	1826	2226	2626	3026
				
	1830	2230	2630	3030
				
	1834	2234	2634	3034
				
	1838	2238	2638	3038
				
	1842	2242	2642	3042

R.O.: Rough Opening
F.S.: Frame Size
H.A.: Height of Awning
V.G.: Visible Glass
V.G.A.: Visible Glass of Awning
V.G.P.: Visible Glass of Picture Unit

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local Lepage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.











Awning windows do not meet Egress requirements.

Venting configurations shown in units of the first line and first column are applicable to all units.

Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq.ft.

PUSH-OUT AWNING WINDOWS

POA100-21

R.O. (mm)	47 7/8" (1216)	55 7/8" (1419)	63 7/8" (1622)	71 7/8" (1826)	79 7/8" (2029)	95 7/8" (2435)
F.S. (mm)	46 7/8" (1191)	54 7/8" (1394)	62 7/8" (1597)	70 7/8" (1800)	78 7/8" (2003)	94 7/8" (2410)
V.G. (mm)	17 7/8" (435)	21 1/2" (546)	25 1/2" (648)	29 1/2" (749)	33 1/2" (851)	41 1/2" (1054)
R.O. (mm)	18 1/2" (470)	20 1/2" (521)	24 1/2" (622)	28 1/2" (724)	32 1/2" (826)	36 1/2" (927)
F.S. (mm)	18" (457)	20" (508)	24" (610)	28" (711)	32" (813)	36" (914)
V.G. (mm)	11 1/2" (293)	13 1/2" (344)	17 1/2" (446)	21 1/2" (547)	25 1/2" (649)	29 1/2" (750)
	 1812	 2212	 2612	 3012	 3412	 4212
	 1814	 2214	 2614	 3014	 3414	 4214
	 1818	 2218	 2618	 3018	 3418	 4218
	 1822	 2222	 2622	 3022	 3422	 4222
	 1826	 2226	 2626	 3026	 3426	 4226
	 1830	 2230	 2630	 3030	 3430	 4230
	 1834	 2234	 2634	 3034	 3434	 4234
	 1842	 2242	 2642	 3042	 3442	 4242

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local Lepage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Awning windows do not meet Egress requirements.























Venting configurations shown in units of the first line and first column are applicable to all units.

PUSH-OUT AWNING WINDOWS

POA100-22

R.O. (mm)	47 7/8" (1216)	55 7/8" (1419)	63 7/8" (1622)	71 7/8" (1826)	79 7/8" (2029)	95 7/8" (2435)
F.S. (mm)	46 7/8" (1191)	54 7/8" (1394)	62 7/8" (1597)	70 7/8" (1800)	78 7/8" (2003)	94 7/8" (2410)
V.G. (mm)	17 3/8" (435)	21 1/2" (546)	25 1/2" (648)	29 1/2" (749)	33 1/2" (851)	41 1/2" (1054)
R.O. (mm)	72 1/2" (1842)	72" (1829)	72" (1829)	72" (1829)	72" (1829)	72" (1829)
F.S. (mm)	72" (1829)	72" (1829)	72" (1829)	72" (1829)	72" (1829)	72" (1829)
V.G. (mm)	29 1/2" (750)	29 1/2" (750)	29 1/2" (750)	29 1/2" (750)	29 1/2" (750)	29 1/2" (750)
	1814	2214	2614	3014	3414	4214
	1818	2218	2618	3018	3418	4218
	1822	2222	2622	3022	3422	4222
	1826	2226	2626	3026	3426	4226
	1830	2230	2630	3030	3430	4230

POA100-2D

R.O. (mm)	78 3/8" (1991)	66 3/8" (1686)	54 3/8" (1381)	48 3/8" (1229)
F.S. (mm)	77 7/8" (1978)	65 7/8" (1674)	53 7/8" (1369)	47 7/8" (1217)
H.A. (mm)	28" (711)	24" (610)	20" (508)	18" (457)
V.G.A. (mm)	21 1/2" (548)	17 1/2" (446)	13 1/2" (344)	11 1/2" (293)
V.G.P. (mm)	43 3/8" (1101)	35 1/2" (898)	27 1/2" (693)	23 1/2" (592)
				
	1822	1818	1814	1812
				
	2222	2218	2214	2212
				
	2622	2618	2614	2612
				
	3022	3018	3014	3012
				
	3422	3418	3414	3412
				
	4222	4218	4214	4212