

PUSH-OUT CASEMENT WINDOWS

POC100-11

Transom	POC100-11						
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318)						
20" (508) 16" (406) 12" (305)							
13 1/2" (343) 9 1/2" (241) 5 1/2" (140)							
R.O. (mm)	17" (432)	19" (483)	21" (533)	25" (635)	29" (736)	33" (838)	37" (940)
F.S. (mm)	16" (406)	18" (457)	20" (508)	24" (610)	28" (711)	32" (813)	36" (914)
V.G. (mm)	9 1/2" (241)	11 1/2" (292)	13 1/2" (343)	17 1/2" (444)	21 1/2" (546)	25 1/2" (638)	29 1/2" (749)
24 1/2" (622)							
28 1/2" (724) 24" (610)							
28" (711)							
32 1/2" (826) 32" (813)							
36 1/2" (927) 36" (914)							
32" (813)							
36" (914)							
29 1/2" (749) 25 1/2" (647)							
35 1/2" (901)							
42 1/2" (1080) 42" (1067)							
48 1/2" (1232) 48" (1219)							
42" (1067)							
48" (1219)							
41 1/2" (1054)							
54 1/2" (1384) 54" (1372)							
47 1/2" (1205)							
60 1/2" (1537) 60" (1524)							
53 1/2" (1358)							
66 1/2" (1689) 66" (1676)							
59 1/2" (1511)							
72 1/2" (1842) 72" (1829)							
65 1/2" (1663)							

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Meets Canadian EGRESS requirements
** Meets U.S. EGRESS requirements

*** Meets U.S. EGRESS requirements with Egress hinge

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Venting configurations shown in units of the first line and first column are applicable to all units.

Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

PUSH-OUT CASEMENT WINDOWS

POC100-21

Transom	20 1/2" (521) 16 1/2" (419) 12 1/2" (318)	20" (508) 16" (406) 12" (305)	13 1/2" (343) 9 1/2" (241) 5 1/2" (140)							
R.O. (mm)	31 7/8" (810)	35 7/8" (912)	39 7/8" (1013)	47 7/8" (1216)	55 7/8" (1420)	63 7/8" (1623)	71 7/8" (1826)			
F.S. (mm)	30 7/8" (785)	34 7/8" (886)	38 7/8" (988)	46 7/8" (1191)	54 7/8" (1394)	62 7/8" (1597)	70 7/8" (1801)			
V.G. (mm)	9 1/2" (241)	11 1/2" (292)	13 1/2" (343)	17 1/2" (444)	21 1/2" (546)	25 1/2" (648)	29 1/2" (749)			
R.O. (mm)	42 1/2" (1080)	48 1/2" (1232)	54 1/2" (1384)	60 1/2" (1537)	66 1/2" (1689)	72 1/2" (1842)				
F.S. (mm)	42" (1067)	48" (1219)	54" (1372)	60" (1524)	66" (1676)	72" (1829)				
V.G. (mm)	35 1/2" (902)	41 1/2" (1055)	47 1/2" (1206)	53 1/2" (1359)	59 1/2" (1512)	65 1/2" (1664)				

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Meets Canadian EGRESS requirements

** Meets U.S. EGRESS requirements

*** Meets U.S. EGRESS requirements with Egress hinge

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Venting configurations shown in units of the first line and first column are applicable to all units.

Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

PUSH-OUT CASEMENT WINDOWS

POC100-31

Transom	20 1/2" (521) 16 1/2" (419) 12 1/2" (318)	20" (508) 16" (406) 12" (305)	13 1/2" (343) 9 1/2" (241) 5 1/2" (140)						
R.O. (mm)	52 3/4" (1340)	58 3/4" (1493)	70 3/4" (1798)	82 3/4" (2102)	94 3/4" (2407)	106 3/4" (2712)			
F.S. (mm)	51 3/4" (1315)	57 3/4" (1467)	69 3/4" (1772)	81 3/4" (2077)	93 3/4" (2382)	105 3/4" (2687)			
V.G. (mm)	11 1/2" (292)	13 1/2" (343)	17 1/2" (444)	21 1/2" (546)	25 1/2" (648)	29 1/2" (749)			

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Meets Canadian EGRESS requirements

** Meets U.S. EGRESS requirements

*** Meets U.S. EGRESS requirements with Egress hinge

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 3/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Venting configurations shown in units of the first line and first column are applicable to all units.

Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

PUSH-OUT CASEMENT WINDOWS

POC100-41

Transom					
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318)				
	20" (508) 16" (406) 12" (305)				
	13 1/2" (343) 9 1/2" (241) 5 1/2" (140)				
R.O. (mm)		77 5/8" (1972)	93 5/8" (2378)	109 5/8" (2785)	125 5/8" (3191)
F.S. (mm)		76 5/8" (1946)	92 5/8" (2353)	108 5/8" (2760)	124 5/8" (3166)
V.G. (mm)		13 1/2" (343)	17 1/2" (444)	21 1/2" (546)	25 1/2" (648)
R.O. (mm)	72 1/2" (1842)				
F.S. (mm)	72" (1829)				
V.G. (mm)	65 1/2" (1663)				
	66 1/2" (1689)				
	66" (1676)				
	59 1/2" (1511)				
	72 1/2" (1842)				
	72" (1829)				
	65 1/2" (1663)				

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Meets Canadian EGRESS requirements
** Meets U.S. EGRESS requirements

*** Meets U.S. EGRESS requirements with Egress hinge

* Please visit our web site for the energy performance of these products at www.lepageimillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all units. Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

PUSH-OUT CASEMENT WINDOWS

POC100-51

Transom	POC100-51			
	1206	1406	1806	2206
20 1/2" (521) 16 1/2" (419) 12 1/2" (318)				
20" (508) 16" (406) 12" (305)				
13 1/2" (342) 9 1/2" (241) 5 1/2" (140)				
R.O. (mm)	86 1/2" (2197)	96 1/2" (2451)	116 1/2" (2960)	136 1/2" (3467)
F.S. (mm)	85 1/2" (2172)	95 1/2" (2426)	115 1/2" (2934)	135 1/2" (3442)
V.G. (mm)	11 1/2" (282)	13 1/2" (343)	17 1/2" (434)	21 1/2" (546)
622				
724				
826				
927				
1080				
1232				
1384				
1537				
1689				
1842				

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Meets Canadian EGRESS requirements
** Meets U.S. EGRESS requirements

*** Meets U.S. EGRESS requirements with Egress hinge































































* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Venting configurations shown in units of the first line and first column are applicable to all units. Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.

PUSH-OUT CASEMENT WINDOWS

POC100-2L

Transom	POC100-2L				
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318) 20" (508) 16" (406) 12" (305) 13 1/2" (342) 9 1/2" (241) 5 1/2" (140)	 1206  1210  1214	 1406  1410  1414	 1806  1810  1814	 2206  2210  2214
R.O. (mm)	47 3/4" (1213)	53 3/4" (1365)	65 3/4" (1670)	77 3/4" (1975)	89 3/4" (2280)
F.S. (mm)	46 3/4" (1187)	52 3/4" (1340)	64 3/4" (1645)	76 3/4" (1949)	88 3/4" (2254)
W.F. (mm)	18" (457)	20" (508)	24" (610)	28" (711)	32" (813)
V.G.F. (mm)	11 1/2" (292)	13 1/2" (343)	17 1/2" (444)	21 1/2" (546)	25 1/2" (648)
V.G.P. (mm)	23 3/8" (594)	27 3/8" (695)	35 3/8" (899)	43 3/8" (1101)	51 3/8" (1305)
24 1/2" (622) 28 1/2" (724) 24" (610) 28" (711) 32 1/2" (826) 28" (711) 32" (813) 36 1/2" (927) 32" (813) 36" (914) 42 1/2" (1080) 36" (914) 42" (1067) 48 1/2" (1232) 42" (1067) 48" (1219) 54 1/2" (1384) 48" (1219) 54" (1372) 60 1/2" (1537) 54" (1372) 60" (1524) 66 1/2" (1689) 60" (1524) 66" (1676) 72" (1829) 66" (1676) 72" (1829) 72 1/2" (1842) 72" (1829) 72" (1829) 65 1/2" (1663) 72" (1829) 65 1/2" (1663)	 1218  1222  1226  1230  1236  1242  1248  1254  1260  1266	 1418  1422  1426  1430  1436  1442  1448  1454  1460  1466	 1818  1822  1826  1830  1836  1842  1848  1854  1860  1866	 2218  2222  2226  2230*  2236*  2242**  2248**  2254**  2260**  2266**	 2618  2622  2626*  2630*  2636**  2642**  2648**  2654**  2660**  2666**

































































R.O.: Rough Opening
 F.S.: Frame Size
 W.F.: Width of Flanker (comparable to the WC11 series)
 V.G.F.: Visible Glass
 V.G.P.: Visible Glass of Flanker
 V.G.P.: Visible Glass of Picture Unit

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com
 Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.
 For masonry openings, please contact your local LePage representative.
 Lite patterns shown are 7/8" (22) SDL. Lite patterns for 3/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.
 Venting configurations shown in units of the first line and first column are applicable to all units.
 Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.
 Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.

* Meets Canadian EGRESS requirements
 ** Meets U.S. EGRESS requirements
 *** Meets U.S. EGRESS requirements with Egress hinge

PUSH-OUT CASEMENT WINDOWS

POC100-3L

Transom	POC100-3L				
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318) 20" (508) 16" (406) 12" (305) 13 1/2" (342) 9 1/2" (241) 5 1/2" (140)	 1206	 1406	 1806	 2206
	 1210	 1410	 1810	 2210	 2610
	 1214	 1414	 1814	 2214	 2614
R.O. (mm)	64 1/2" (1638)	72 1/2" (1842)	88 1/2" (2248)	104 1/2" (2654)	120 1/2" (3061)
F.S. (mm)	63 1/2" (1613)	71 1/2" (1816)	87 1/2" (2223)	103 1/2" (2629)	119 1/2" (3035)
W.F. (mm)	18" (457)	20" (508)	24" (610)	28" (711)	32" (813)
V.G.F. (mm)	11 1/2" (292)	13 1/2" (343)	17 1/2" (444)	21 1/2" (546)	25 1/4" (648)
V.G.P. (mm)	23 1/4" (590)	27 1/4" (692)	35 1/4" (895)	43 1/4" (1099)	51 1/4" (1301)
	 1218	 1418	 1818	 2218	 2618
	 1222	 1422	 1822	 2222	 2622
	 1226	 1426	 1826	 2226	 2626*
	 1230	 1430	 1830	 2230*	 2630*
	 1236	 1436	 1836	 2236*	 2636**
	 1242	 1442	 1842	 2242***	 2642**
	 1248	 1448	 1848	 2248***	 2648**
	 1254	 1454	 1854	 2254***	 2654**
	 1260	 1460	 1860	 2260***	 2660**
	 1266	 1466	 1866	 2266***	 2666**

R.O.: Rough Opening
 F.S.: Frame Size
 W.F.: Width of Flanker (comparable to the WC11 series)
 V.G.: Visible Glass
 V.G.F.: Visible Glass of Flanker
 V.G.P.: Visible Glass of Picture Unit

* Please visit our web site for the energy performance of these products at www.lepageinc.com
 Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.
 For masonry openings, please contact your local LePage representative.
 Lite patterns shown are 3/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.
 Venting configurations shown in units of the first line and first column are applicable to all units.
 Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.
 Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.

* Meets Canadian EGRESS requirements
 ** Meets U.S. EGRESS requirements
 *** Meets U.S. EGRESS requirements with Egress hinge

PUSH-OUT CASEMENT WINDOWS

POC100-P

Transom	POC100-P				
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318) 20" (508) 16" (406) 12" (305) 13 1/2" (342) 9 1/2" (241) 5 1/2" (140)				
	2410	2810	3610	4410	5210
	2414	2814	3614	4414	5214
R.O. (mm)	31" (787)	35" (889)	43" (1092)	51" (1295)	59" (1498)
F.S. (mm)	30" (761)	34" (863)	42" (1066)	50" (1269)	58" (1473)
V.G. (mm)	23 1/2" (596)	27 1/2" (697)	35 1/2" (901)	43 1/2" (1104)	51 1/2" (1307)
R.O. (mm)	24 1/2" (622)	28 1/2" (724)	36 1/2" (927)	42 1/2" (1080)	48 1/2" (1232)
F.S. (mm)	24" (610)	28" (711)	32" (813)	36" (914)	42" (1067)
V.G. (mm)	17 1/2" (444)	21 1/2" (546)	25 1/2" (647)	29 1/2" (749)	35 1/2" (901)
	2418	2818	3618	4418	5218
	2422	2822	3622	4422	5222
	2426	2826	3626	4426	5226
	2430	2830	3630	4430	5230
	2436	2836	3635	4436	5236
	2442	2842	3642	4442	5242
	2448	2848	3648	4448	5248
	2454	2854	3654	4454	5254
	2460	2860	3660	4460	5260
	2466	2866	3666	4466	5266

R.O.: Rough Opening
 F.S.: Frame Size
 V.G.: Visible Glass

* Please visit our web site for the energy performance of these products at www.lepageillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

All these units are shown stationary as standard transoms or picture units.

Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq.ft.

FRENCH PUSH-OUT CASEMENT WINDOWS

FPOC100-21

Transom	R.O. (mm)						
	20 1/2" (521) 16 1/2" (419) 12 1/2" (318)	31 7/8" (810)	35 7/8" (912)	39 7/8" (1013)	47 7/8" (1216)	55 7/8" (1420)	63 7/8" (1623)
20" (508) 16" (406) 12" (305)	30 7/8" (785)	34 7/8" (886)	38 7/8" (988)	46 7/8" (1191)	54 7/8" (1394)	62 7/8" (1597)	70 7/8" (1801)
13 1/8" (341) 9 1/8" (239) 5 1/8" (137)	10 1/8" (255)	12 1/8" (306)	14 1/8" (357)	18 1/8" (458)	22 1/8" (560)	26 1/8" (661)	30 1/8" (763)

R.O. (mm)	F.S. (mm)						
	66 1/2" (1689)	60 1/2" (1537)	54 1/2" (1384)	48 1/2" (1232)	42 1/2" (1080)	36 1/2" (927)	32 1/2" (826)
66" (1676)	60" (1524)	54" (1372)	48" (1219)	42" (1067)	36" (914)	32" (813)	28" (711)
65 7/16" (1662)	59 7/16" (1510)	53 7/16" (1357)	47 7/16" (1205)	41 7/16" (1053)	35 7/16" (899)	29 7/16" (747)	25 7/16" (645)

R.O. (mm)	F.S. (mm)						
	72 1/2" (1842)	72" (1829)	65 7/16" (1662)	59 7/16" (1510)	53 7/16" (1357)	47 7/16" (1205)	41 7/16" (1053)
72" (1829)	65 7/16" (1662)	59 7/16" (1510)	53 7/16" (1357)	47 7/16" (1205)	41 7/16" (1053)	35 7/16" (899)	29 7/16" (747)
65 7/16" (1662)	59 7/16" (1510)	53 7/16" (1357)	47 7/16" (1205)	41 7/16" (1053)	35 7/16" (899)	29 7/16" (747)	25 7/16" (645)

Transom	1006	1206	1406	1806	2206	2606	3006
20 1/2" (521) 16 1/2" (419) 12 1/2" (318)							
20" (508) 16" (406) 12" (305)							
13 1/8" (341) 9 1/8" (239) 5 1/8" (137)							

Transom	1018	1218	1418	1818	2218	2618	3018
24" (610)							
28" (711)							
28" (711)							
32" (813)							
32" (813)							
36" (914)							
36" (914)							
42" (1067)							
42" (1067)							
48" (1219)							

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Meets Canadian EGRESS requirements

** Meets U.S. EGRESS requirements

*** Meets U.S. EGRESS requirements with Egress hinge

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

Venting configurations shown in units of the first line and first column are applicable to all units.

Units with 12" (305), 16" (406) and 20" (508) heights are shown stationary as standard transoms.