

Double Hung Window XL-100 – Aluminium clad

Frame:

- Pine, red grandis or mahogany
- Aluminium clad, extruded 0.060", 1.5mm thick
- Thickness 1 ¼" (32mm) and interior facing including the sash stop : 1 7/8" (48mm)
- Depth 5 9/16" (141mm)

Sash:

- Pine, red grandis or mahogany
- Aluminium clad, extruded 0.060", 1.5mm thick
- Thickness 1 ¾" (44.5mm)
- Height: 1 13/16" (46mm) / 3 ¼" (82mm)

Interior finish:

- Natural, primed, first coat, Lepage stain or paint over 50 colors

Exterior finish:

- Lepage paint over 50 colors

Hardware:

- Surface mount: satin nickel, unlaquered brass, polish brass, polish nickel or oil rubbed bronze
- Hybride balance lite-lift class 5
- Sash limiter options

Weather-strip

- Silicone, Q-Lon

Insulated glass:

- Double glaze ¾" (19 mm)
- "Technoform" spacer, bronze, white, black.
- Argon

Glass available:

- Clear, grey, bronze, pinhead, glue-chip
- Low-e: Energy advantage, 272, 366, 189
- Tempered
- Laminated

Screen:

- Mesh: invisible fiberglass, grey or black aluminium
- Surround: white, coppertone or Lepage paint over 50 colors
- Wood screen surround
- Retractable

Grilles:

- Internal georgian $\frac{3}{4}$ ", 1" or 1 $\frac{3}{4}$ "
- Internal flat $\frac{5}{16}$ ", $\frac{5}{8}$ ", $\frac{3}{4}$ " or 1"
- Internal tubular: white, brass or pewter

Simulated Divided Lites (SDL):

- $\frac{5}{8}$ ", $\frac{7}{8}$ ", 1 $\frac{1}{4}$ " or 1 $\frac{3}{4}$ "
- Spacer bars bronze, white or black

Casing:

- 908
- 1 $\frac{3}{4}$ ", 2 $\frac{3}{4}$ " and 3 $\frac{1}{2}$ " Flat casing
- 3 $\frac{15}{16}$ " Backbend (D-090)
- Skyler
- Nailing fin

Sill Extension:

- Standard D-082 (1" x 1 $\frac{1}{4}$ ")
- Historic D-083 (1 $\frac{3}{4}$ " x 2")

Interior Jamb Extension:

- Finish and wood species same as interior frame 1/8" min and 6" max

Minimums and Maximums:

Minimum width:	12"	Maximum width:	66"
Minimum height:	26"	Maximum height:	152"

Maximum: 43 square foot – (frame size) for double IG

Maximum of 97 lbs per sash

For more information, please visit our web site at www.lepagemillwork.com