



Aluminum Clad Wood Direct Set

Manu-Data

Frame :

Non Finger-Jointed Pine, Red Grandis or Mahogany

Thickness : 1 1/8" (28 mm)

Depth : 4 9/16" (116mm) or 6 9/16" (167 mm)

Extruded Aluminium cladding, 0.060 " (1.5 mm) thick

Interior Finish :

-Natural, primed, first coat, Lepage stain or paint over 50 colors

Exterior Finish :

-Natural, primed, first coat, Lepage stain or paint over 50 colors

Insulated Glass :

- 2 step barrier installation : foam tape and wet glaze

-Double Glaze 3/4" (19 mm)

- Triple Glaze 1 1/4" (32mm) available with 2 1/4" (57mm) sash

-Spacer : "Technoform" bronze, white, grey, black

-Argon

Ohters Glass options :

-Clear, grey, bronze, pinhead, glue-chip

-Low-e: Energy advantage, 272, 366, 189

-Tempered

-Laminated

LEPAGE MILLWORK

lepagemillwork.com



Grilles options :

Wide options of grilles between glass (GBG), simulate divided light (SDL) and true divided light (TDL)

[See website for all options](#)

Casing and sill extensions :

[See website for all options](#)

Custom casing also available on request

Minimum and maximum sizes :

Minimum Width : 6" per section

Maximum Width : 144" per section

Minimum Height : 6" par section

Maximum Height : 144" per section

Maximum IG area : 60 ft²

[See our website for more information : www.lepagemillwork.com](http://www.lepagemillwork.com)