



Aluminum Clad Wood Push-Out Casement

Manu-Data

Frame :

Non Finger-Jointed Pine, Red Grandis or Mahogany
Thickness : 1 1/8" (28 mm)
Depth with 1 3/4" sash : 4 9/16" (116mm) or 6 9/16" (167mm)
Depth with 2 1/4" : 5 1/16" (129mm) or 7 1/16 (179 mm)
Extruded Aluminium cladding, 0.060 " (1.5 mm) thick

Sash :

Non Finger-Jointed Pine, Red Grandis or Mahogany
Thickness of 1 3/4" (44,5 mm) or 2 1/4" (57mm)
Colonial or Putty glaze Profile
Extruded Aluminium cladding, 0.060 " (1.5 mm) thick

Hardware :

Traditionnal or Classic Handle
Multipoint lock system
Casement stay
Many colors options, see website
Frictions Hinges : Egress, Standard or Heavy Duty
Note : the heavy duty hinge is not with friction, so casement stay always required.

Weather Stripping :

2 step barrier :
Wind breaker made of black polyflex
8 mm silicone bulb weather strip

Interior Finish :

-Natural, primed, first coat, Lepage stain or paint over 50 colors

Exterior Finish :

-Natural, primed, first coat, Lepage stain or paint over 50 colors

Insulated Glass :

-Double Glaze 3/4" (19 mm)
- Triple Glaze 1 1/4" (32mm) available with 2 1/4" (57mm) sash
-Spacer : "Technoform" bronze, white, grey, black
-Argon
Ohters Glass options :
-Clear, grey, bronze, pinhead, glue-chip
-Low-e: Energy advantage, 272, 366, 189
-Tempered
-Laminated

LEPAGE MILLWORK

lepagemillwork.com



Screen:

- Mesh: invisible fiberglass, grey or black aluminium
- Surround: white, coppertone, beige, oil rubbed bronze or black
- Wood screen surround
- Retractable

Grilles options :

Wide options of grilles between glass (GBG), simulate divided light (SDL) and true divided light (TDL)

[See website for all options](#)

Casing and sill extensions :

[See website for all options](#)

Custom casing also available on request

Minimum and maximum sizes for windows with 1 ¾" sash:

Minimum Width : 14" or 18" with casement stay per section

Maximum Width : 40" per section

Minimum Height : 14" par section

Maximum Height : 84" per section

Minimum and maximum sizes for French Push Out Casement :

Minimum Width : 25" per section

Maximum Width : 72" per section

Minimum Height : 26.5" par section

Maximum Height : 84" per section

Maximum weight per sash : 130 lbs.

[See our website for more information : www.lepagemillwork.com](http://www.lepagemillwork.com)