



Wood Push-Out Awning

Manu-Data

Frame :

Non Finger-Jointed Pine, Red Grandis or Mahogany

Thickness : 1 1/8" (28 mm)

Depth : 4 9/16" (116mm)

Depth : 5 1/16" (129mm) with 2 1/4" sash

Sash :

Non Finger-Jointed Pine, Red Grandis or Mahogany

Thickness of 1 3/4" (44,5 mm) or 2 1/4" (57mm)

Colonial or Putty Glaze Profile

Wide or narrow bottom rails options

Hardware :

Traditionnal or Classic Handle

Single lock system on both side

Casement stay

Many colors options, see website

Frictions Hinges

Weather Stripping :

2 step barrier :

Wind breaker made of black polyflex

8 mm silicone bulb weather strip

Interior Finish :

-Natural, primed, first coat, Lepage stain or paint over 50 colors

Exterior Finish :

-Natural, primed, first coat, Lepage stain or paint over 50 colors

Insulated Glass :

-Double Glaze 3/4" (19 mm)

- Triple Glaze 1 1/4" (32mm) available with 2 1/4" (57mm) sash

-Spacer : "Technoform" bronze, white, grey, black

-Argon

Ohters Glass options :

-Clear, grey, bronze, pinhead, glue-chip

-Low-e: Energy advantage, 272, 366, 189

-Tempered

-Laminated

LEPAGE MILLWORK

lepagemillwork.com



Screen:

- Mesh: invisible fiberglass, grey or black aluminium
- Surround: white, coppertone, beige, oil rubbed bronze or black
- Wood screen surround
- Retractable

Grilles options :

Wide options of grilles between glass (GBG), simulate divided light (SDL) and true divided light (TDL)

[See website for all options](#)

Casing and sill extensions :

[See website for all options](#)

Custom casing also available on request

Minimum and maximum sizes for windows with 1 3/4" or 2 1/4" sash:

Minimum Width : 14" per section

Maximum Width : 52" per section

Minimum Height : 14" par section

Maximum Height : 48" per section

Maximum weight per sash : 120 lbs.

[See our website for more information : www.lepagemillwork.com](http://www.lepagemillwork.com)