



Aluminium Clad Wood Inswing

Manu-Data

Frame :

Non Finger-Jointed Pine, Red Grandis or Mahogany
Thickness : 1 1/4" (32 mm)
Depth : 4 3/8" (136mm)
Extruded Aluminium cladding, 0.060 " (1.5 mm) thick

Sash :

Non Finger-Jointed Pine, Red Grandis or Mahogany
Thickness of 1 3/4" (44,5 mm)
Colonial or Putty Glaze Profile
Extruded Aluminium cladding, 0.060 " (1.5 mm) thick

Hardware :

Rustic or classic cremone and hinges
Many colors options, see website

Weather Stripping :

Silicone
8 mm silicone bulb weather strip

Interior Finish :

-Natural, primed, first coat, Lepage stain or paint over 50 colors

Exterior Finish :

-Natural, primed, first coat, Lepage stain or paint over 50 colors

Insulated Glass :

-Double Glaze 3/4" (19 mm)
-Spacer : "Technoform" bronze, white, grey, black
-Argon
Ohters Glass options :
-Clear, grey, bronze, pinhead, glue-chip
-Low-e: Energy advantage, 272, 366, I89
-Tempered
-Laminated

LEPAGE MILLWORK

lepagemillwork.com



Screen:

- Mesh: invisible fiberglass, grey or black aluminium
- Surround: white, coppertone, beige, oil rubbed bronze or black
- Wood screen surround

Grilles options :

Wide options of grilles between glass (GBG), simulate divided light (SDL) and true divided light (TDL)

[See website for all options](#)

Casing and sill extensions :

[See website for all options](#)

Custom casing also available on request

Minimum and maximum sizes for windows with simple sash:

Minimum Width : 15" per section
Maximum Width : 42" per section
Minimum Height : 20" per section
Maximum Height : 96" per section

Minimum and maximum sizes for windows with double sash:

Minimum Width : 28" per section
Maximum Width : 84" per section
Minimum Height : 20" per section
Maximum Height : 96" per section

Maximum 21 sq ft (IG)

[See our website for more information : www.lepagemillwork.com](http://www.lepagemillwork.com)