

## CLAD WOOD MULTISLIDE DOOR - 2 1/4" PANEL - 3 5/8" Stiles &amp; Rails

**LEPAGE**  
MILLWORK

## ENERGY DATA

| I.G.                                                  | U Factor<br>(w/m <sup>2</sup> *K) | U Factor<br>(Bth/h*ft <sup>2</sup> *) | SHGC | VT   | CR | R Value | ER | Energy Star Canada V5 -<br>2020 | Energy Star USA V7 - 2023 |
|-------------------------------------------------------|-----------------------------------|---------------------------------------|------|------|----|---------|----|---------------------------------|---------------------------|
| Clad 5in_SM_ClrPNA-Arg95-LOF#3                        | 1,82                              | 0,32                                  | 0,46 | 0,46 | 52 | 3,15    | 27 | -                               | -                         |
| Clad 5in_SM_ClrPNA-Arg95-LOF#3_SDL WSB 1/4"           | 1,82                              | 0,32                                  | 0,40 | 0,40 | 52 | 3,15    | 23 | -                               | -                         |
| Clad 5in_SM_ClrPNA-Arg95-LOF#3_SDL WSB 3/8"           | 1,87                              | 0,33                                  | 0,40 | 0,40 | 51 | 3,00    | 22 | -                               | -                         |
| Clad 5in_SM_LOF#2-Arg95-i89#4                         | 1,59                              | 0,28                                  | 0,40 | 0,45 | 40 | 3,61    | 28 | -                               | -                         |
| Clad 5in_SM_LOF#2-Arg95-i89#4_SDL WSB 1/4"            | 1,65                              | 0,29                                  | 0,35 | 0,39 | 40 | 3,43    | 24 | -                               | -                         |
| Clad 5in_SM_LOF#2-Arg95-i89#4_SDL WSB 3/8"            | 1,7                               | 0,30                                  | 0,35 | 0,39 | 40 | 3,28    | 23 | -                               | -                         |
| Clad 5in_SM_272#2-Arg95-ClrCGI                        | 1,65                              | 0,29                                  | 0,25 | 0,43 | 52 | 3,43    | 18 | -                               | -                         |
| Clad 5in_SM_272#2-Arg95-ClrCGI_SDL WSB 1/4"           | 1,65                              | 0,29                                  | 0,22 | 0,37 | 52 | 3,43    | 16 | -                               | -                         |
| Clad 5in_SM_272#2-Arg95-ClrCGI_SDL WSB 3/8"           | 1,76                              | 0,31                                  | 0,22 | 0,37 | 52 | 3,23    | 14 | -                               | -                         |
| Clad 5in_SM_272#2-Arg95-i89#4                         | 1,48                              | 0,26                                  | 0,25 | 0,42 | 43 | 3,86    | 22 | -                               | N,NC                      |
| Clad 5in_SM_272#2-Arg95-i89#4_SDL WSB 1/4"            | 1,53                              | 0,27                                  | 0,22 | 0,36 | 43 | 3,68    | 19 | -                               | SC,S                      |
| Clad 5in_SM_272#2-Arg95-i89#4_SDL WSB 3/8"            | 1,65                              | 0,29                                  | 0,22 | 0,36 | 43 | 3,48    | 16 | -                               | -                         |
| Clad 5in_SM_366#2-Arg95-ClrCGI                        | 1,65                              | 0,29                                  | 0,17 | 0,39 | 53 | 3,49    | 13 | -                               | -                         |
| Clad 5in_SM_366#2-Arg95-ClrCGI_SDL WSB 1/4"           | 1,65                              | 0,29                                  | 0,15 | 0,33 | 53 | 3,49    | 12 | -                               | -                         |
| Clad 5in_SM_366#2-Arg95-ClrCGI_SDL WSB 3/8"           | 1,7                               | 0,30                                  | 0,15 | 0,33 | 53 | 3,28    | 11 | -                               | -                         |
| Clad 5in_SM_366#2-Arg95-i89#4                         | 1,48                              | 0,26                                  | 0,17 | 0,38 | 43 | 3,91    | 17 | -                               | N,NC,SC,S                 |
| Clad 5in_SM_366#2-Arg95-i89#4_SDL WSB 1/4"            | 1,53                              | 0,27                                  | 0,15 | 0,32 | 43 | 3,74    | 15 | -                               | SC,S                      |
| Clad 5in_SM_366#2-Arg95-i89#4_SDL WSB 3/8"            | 1,59                              | 0,28                                  | 0,15 | 0,32 | 43 | 3,52    | 14 | -                               | -                         |
| Clad 5in_SM_CG70#2-Arg95-ClrGIG                       | 1,65                              | 0,29                                  | 0,22 | 0,41 | 53 | 3,48    | 16 | -                               | -                         |
| Clad 5in_SM_CG70#2-Arg95-ClrGIG_SDL WSB 1/4"          | 1,65                              | 0,29                                  | 0,19 | 0,35 | 53 | 3,48    | 15 | -                               | -                         |
| Clad 5in_SM_CG70#2-Arg95-ClrGIG_SDL WSB 3/8"          | 1,76                              | 0,31                                  | 0,19 | 0,35 | 53 | 3,27    | 12 | -                               | -                         |
| Clad 5in_SM_CG70#2-Arg95-IS20#4                       | 1,48                              | 0,26                                  | 0,21 | 0,40 | 44 | 3,85    | 20 | -                               | N,NC,SC,S                 |
| Clad 5in_SM_CG70#2-Arg95-IS20#4_SDL WSB 1/4"          | 1,53                              | 0,27                                  | 0,18 | 0,34 | 44 | 3,70    | 17 | -                               | SC,S                      |
| Clad 5in_SM_CG70#2-Arg95-IS20#4_SDL WSB 3/8"          | 1,65                              | 0,29                                  | 0,18 | 0,34 | 44 | 3,49    | 14 | -                               | -                         |
| Clad 5in_SM_Clr/PVB0 015/Clr-Arg95-LOF#3              | 1,82                              | 0,32                                  | 0,41 | 0,45 | 53 | 3,16    | 24 | -                               | -                         |
| Clad 5in_SM_Clr/PVB0 015/Clr-Arg95-LOF#3_SDL WSB 1/4" | 1,82                              | 0,32                                  | 0,35 | 0,39 | 53 | 3,16    | 20 | -                               | -                         |
| Clad 5in_SM_Clr/PVB0 015/Clr-Arg95-LOF#3_SDL WSB 3/8" | 1,82                              | 0,32                                  | 0,35 | 0,39 | 53 | 3,16    | 20 | -                               | -                         |
| Clad 5in_SM_272#2-Arg95-Clr/PVB0 015/Clr              | 1,65                              | 0,29                                  | 0,25 | 0,42 | 55 | 3,43    | 18 | -                               | -                         |
| Clad 5in_SM_272#2-Arg95-Clr/PVB0 015/Clr_SDL WSB 1/4" | 1,65                              | 0,29                                  | 0,22 | 0,36 | 55 | 3,43    | 16 | -                               | -                         |
| Clad 5in_SM_272#2-Arg95-Clr/PVB0 015/Clr_SDL WSB 3/8" | 1,65                              | 0,29                                  | 0,22 | 0,36 | 55 | 3,43    | 16 | -                               | -                         |

|                                                          |      |      |      |      |    |      |    |     |           |
|----------------------------------------------------------|------|------|------|------|----|------|----|-----|-----------|
| Clad 5in_SM_366#2-Arg95-Clr/PVB0[015/Clr                 | 1,65 | 0,29 | 0,17 | 0,38 | 55 | 3,49 | 13 | -   | -         |
| Clad 5in_SM_366#2-Arg95-Clr/PVB0[015/Clr SDL WSB 1/4"    | 1,65 | 0,29 | 0,15 | 0,33 | 55 | 3,49 | 12 | -   | -         |
| Clad 5in_SM_366#2-Arg95-Clr/PVB0[015/Clr SDL WSB 3/8"    | 1,65 | 0,29 | 0,15 | 0,33 | 55 | 3,49 | 12 | -   | -         |
| Clad 5in_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5              | 1,53 | 0,27 | 0,42 | 0,42 | 60 | 3,77 | 31 | -   | -         |
| Clad 5in_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5 SDL WSB 1/4" | 1,53 | 0,27 | 0,36 | 0,36 | 60 | 3,66 | 27 | -   | -         |
| Clad 5in_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5 SDL WSB 3/8" | 1,59 | 0,28 | 0,36 | 0,36 | 60 | 3,53 | 26 | -   | -         |
| Clad 5in_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5               | 1,36 | 0,24 | 0,40 | 0,40 | 62 | 4,18 | 33 | -   | N,NC      |
| Clad 5in_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5 SDL WSB 1/4"  | 1,42 | 0,25 | 0,34 | 0,34 | 62 | 4,04 | 28 | -   | N,NC      |
| Clad 5in_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5 SDL WSB 3/8"  | 1,48 | 0,26 | 0,34 | 0,34 | 62 | 3,89 | 27 | -   | N,NC      |
| Clad 5in_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI              | 1,42 | 0,25 | 0,24 | 0,39 | 61 | 3,96 | 23 | -   | N,NC      |
| Clad 5in_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI SDL WSB 1/4" | 1,48 | 0,26 | 0,21 | 0,34 | 61 | 3,83 | 20 | -   | SC,S      |
| Clad 5in_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI SDL WSB 3/8" | 1,53 | 0,27 | 0,21 | 0,34 | 61 | 3,69 | 18 | -   | SC,S      |
| Clad 5in_SM_272#2-Arg95-ClrCGI-Arg95-272#5               | 1,25 | 0,22 | 0,22 | 0,34 | 64 | 4,55 | 25 | -   | N,NC,SC,S |
| Clad 5in_SM_272#2-Arg95-ClrCGI-Arg95-272#5 SDL WSB 1/4"  | 1,31 | 0,23 | 0,19 | 0,29 | 64 | 4,35 | 22 | -   | N,NC,SC,S |
| Clad 5in_SM_272#2-Arg95-ClrCGI-Arg95-272#5 SDL WSB 3/8"  | 1,36 | 0,24 | 0,19 | 0,29 | 64 | 4,17 | 21 | -   | N,NC,SC,S |
| Clad 5in_SM_272#2-Arg95-272#4-Arg95-i89#6                | 1,19 | 0,21 | 0,20 | 0,34 | 55 | 4,81 | 25 | Oui | N,NC,SC,S |
| Clad 5in_SM_272#2-Arg95-272#4-Arg95-i89#6 SDL WSB 1/4"   | 1,25 | 0,22 | 0,17 | 0,29 | 55 | 4,46 | 22 | -   | N,NC,SC,S |
| Clad 5in_SM_272#2-Arg95-272#4-Arg95-i89#6 SDL WSB 3/8"   | 1,31 | 0,23 | 0,17 | 0,29 | 55 | 4,29 | 21 | -   | N,NC,SC,S |
| Clad 5in_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI              | 1,42 | 0,25 | 0,16 | 0,35 | 61 | 4,01 | 18 | -   | N,NC,SC,S |
| Clad 5in_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI SDL WSB 1/4" | 1,48 | 0,26 | 0,14 | 0,30 | 61 | 3,87 | 15 | -   | N,NC,SC,S |
| Clad 5in_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI SDL WSB 3/8" | 1,53 | 0,27 | 0,14 | 0,30 | 61 | 3,73 | 14 | -   | SC,S      |
| Clad 5in_SM_366#2-Arg95-ClrCGI-Arg95-366#5               | 1,25 | 0,22 | 0,15 | 0,28 | 65 | 4,63 | 21 | -   | N,NC,SC,S |
| Clad 5in_SM_366#2-Arg95-ClrCGI-Arg95-366#5 SDL WSB 1/4"  | 1,31 | 0,23 | 0,13 | 0,24 | 64 | 4,42 | 19 | -   | N,NC,SC,S |
| Clad 5in_SM_366#2-Arg95-ClrCGI-Arg95-366#5 SDL WSB 3/8"  | 1,36 | 0,24 | 0,13 | 0,24 | 64 | 4,23 | 18 | -   | N,NC,SC,S |

Cl : Vitre clair / Clear glass

LOF : Low-E Energy Adv.

\* Depending on the options chosen, this product can meet Energy Star specifications for your area

#### Notes :

Product Values are determined using the National Fenestration Rating Council (NFRC) Procedures for determining fenestration product values. Values are subject to update and can vary depending on the options chosen.

U-Factor : (btu/h\*ft²F) The lower the U-Factor, the greater the resistance to heat flow and the better the insulating value will be.

SHGC : Solar Heat Gain Coefficient, the lower a window's SHGC, the less solar heat it transmits, and the greater its shading ability.

Visible Transmittance (VT) : Percentage of visible light transmitted.

R-Value : (1/U-Value) A higher R-Value increase the resistance to heat flow, resultin a better insulating value.

ER : Energy Rating, this value is calculated with the U-Factor, SHGC and air infiltration of the product. The higher the ER, the better the product will be for the Northern zones and the lower the ER, the better the produt will be for Southern zones.

