

POC-100 ALUMINIUM CLAD PUSH-OUT CASEMENT - 2 1/4" SASH (operating)

LEPAGE
MILLWORK


ENERGY DATA

I.G.	U Factor (w/m ² *K)	U Factor (Bth/h*ft ² *)	SHGC	VT	CR	R Value	ER	Energy Star Canada V5 - 2020	Energy Star USA V7 2023
PO_Clad_2 25_SM_ClrPNA-Arg95-LOF#3	1.82	0.32	0.49	0.49	55	3.08	28	-	-
PO_Clad_2 25_SM_ClrPNA-Arg95-LOF#3 SDL WSB 1/4"	1.82	0.32	0.45	0.44	55	3.08	26	-	-
PO_Clad_2 25_SM_ClrPNA-Arg95-LOF#3 SDL WSB 3/8"	1.93	0.34	0.45	0.44	55	2.98	24	-	-
PO_Clad_2 25_SM_LOF#2-Arg95-i89#4	1.59	0.28	0.43	0.48	43	3.53	30	-	-
PO_Clad_2 25_SM_LOF#2-Arg95-i89#4 SDL WSB 1/4"	1.65	0.29	0.39	0.43	43	3.42	26	-	-
PO_Clad_2 25_SM_LOF#2-Arg95-i89#4 SDL WSB 3/8"	1.70	0.30	0.39	0.43	43	3.30	25	-	-
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI	1.70	0.30	0.27	0.46	57	3.36	18	-	-
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI SDL WSB 1/4"	1.70	0.30	0.25	0.42	57	3.36	17	-	-
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI SDL WSB 3/8"	1.76	0.31	0.25	0.42	57	3.22	16	-	-
PO_Clad_2 25_SM_272#2-Arg95-i89#4	1.48	0.26	0.27	0.45	45	3.78	23	-	-
PO_Clad_2 25_SM_272#2-Arg95-i89#4 SDL WSB 1/4"	1.53	0.27	0.24	0.41	45	3.67	20	-	-
PO_Clad_2 25_SM_272#2-Arg95-i89#4 SDL WSB 3/8"	1.59	0.28	0.24	0.41	45	3.52	19	-	-
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI	1.65	0.29	0.18	0.41	58	3.42	14	-	-,-,-,S
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI SDL WSB 1/4"	1.65	0.29	0.17	0.37	58	3.42	13	-	-,-,-,S
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI SDL WSB 3/8"	1.76	0.31	0.17	0.37	58	3.27	11	-	-,-,-,S
PO_Clad_2 25_SM_366#2-Arg95-i89#4	1.48	0.26	0.18	0.41	46	3.84	18	-	-,-,SC,S
PO_Clad_2 25_SM_366#2-Arg95-i89#4 SDL WSB 1/4"	1.53	0.27	0.16	0.37	46	3.73	16	-	-,-,SC,S
PO_Clad_2 25_SM_366#2-Arg95-i89#4 SDL WSB 3/8"	1.59	0.28	0.16	0.37	46	3.57	14	-	-,-,-,S
PO_Clad_2 25_SM_Clr/PVB0 015/Clr-Arg95-LOF#3	1.93	0.34	0.43	0.48	52	2.91	22	-	-
PO_Clad_2 25_SM_Clr/PVB0 015/Clr-Arg95-LOF#3 SDL WSB 1/4"	2.04	0.36	0.39	0.44	52	2.77	18	-	-
PO_Clad_2 25_SM_Clr/PVB0 015/Clr-Arg95-LOF#3 SDL WSB 3/8"	2.27	0.40	0.39	0.44	44	2.50	13	-	-
PO_Clad_2 25_SM_272#2-Arg95-Clr/PVB0 015/Clr	1.82	0.32	0.27	0.45	54	3.15	16	-	-
PO_Clad_2 25_SM_272#2-Arg95-Clr/PVB0 015/Clr SDL WSB 1/4"	1.93	0.34	0.25	0.41	54	2.97	12	-	-
PO_Clad_2 25_SM_272#2-Arg95-Clr/PVB0 015/Clr SDL WSB 3/8"	2.16	0.38	0.25	0.41	47	2.64	7	-	-
PO_Clad_2 25_SM_366#2-Arg95-Clr/PVB0 015/Clr	1.76	0.31	0.18	0.41	54	3.20	12	-	-,-,-,S
PO_Clad_2 25_SM_366#2-Arg95-Clr/PVB0 015/Clr SDL WSB 1/4"	1.87	0.33	0.17	0.37	54	3.01	9	-	-
PO_Clad_2 25_SM_366#2-Arg95-Clr/PVB0 015/Clr SDL WSB 3/8"	2.16	0.38	0.17	0.37	47	2.67	2	-	-
PO_Clad_2 25_SM_Clr/SGP0.090/Clr-Arg95-LOF#3	1.82	0.32	0.42	0.48	54	3.08	24	-	-
PO_Clad_2 25_SM_Clr/SGP0.090/Clr-Arg95-LOF#3 SDL WSB 1/4"	1.93	0.34	0.38	0.43	54	2.98	19	-	-
PO_Clad_2 25_SM_Clr/SGP0.090/Clr-Arg95-LOF#3 SDL WSB 3/8"	1.99	0.35	0.38	0.43	54	2.88	18	-	-

PO_Clad_2 25_SM_Clr/PVB0.090/272-Arg95-ClrCGI	1.70	0.30	0.26	0.44	57	3.36	18	-	-
PO_Clad_2 25_SM_Clr/PVB0.090/272-Arg95-ClrCGI_SDL WSB 1/4"	1.76	0.31	0.24	0.40	57	3.22	15	-	-
PO_Clad_2 25_SM_Clr/PVB0.090/272-Arg95-ClrCGI_SDL WSB 3/8"	1.82	0.32	0.24	0.40	57	3.10	14	-	-
PO_Clad_2 25_SM_Clr/PVB0.090/366-Arg95-ClrCGI	1.65	0.29	0.18	0.40	57	3.42	14	-	-,-,-,S
PO_Clad_2 25_SM_Clr/PVB0.090/366-Arg95-ClrCGI_SDL WSB 1/4"	1.76	0.31	0.17	0.36	57	3.27	11	-	-,-,-,S
PO_Clad_2 25_SM_Clr/PVB0.090/366-Arg95-ClrCGI_SDL WSB 3/8"	1.82	0.32	0.17	0.36	57	3.14	10	-	-,-,-,S
PO_Clad_2 25_SM_Clr/PVB0 015/Clr-Arg95-LOF#3_25	1.82	0.32	0.44	0.48	56	3.11	25	-	-
PO_Clad_2 25_SM_Clr/PVB0 015/Clr-Arg95-LOF#3_25_SDL WSB 3/8"	1.82	0.32	0.40	0.44	56	3.11	23	-	-
PO_Clad_2 25_SM_Clr/PVB0 015/Clr-Arg95-LOF#3_25_SDL WSB 1/4"	1.82	0.32	0.40	0.44	56	3.11	23	-	-
PO_Clad_2 25_SM_272#2-Arg95-Clr/PVB0 015/Clr_25	1.65	0.29	0.27	0.45	58	3.39	19	-	-
PO_Clad_2 25_SM_272#2-Arg95-Clr/PVB0 015/Clr_25_SDL WSB 3/8"	1.65	0.29	0.25	0.41	58	3.39	18	-	-
PO_Clad_2 25_SM_272#2-Arg95-Clr/PVB0 015/Clr_25_SDL WSB 1/4"	1.65	0.29	0.25	0.41	58	3.39	18	-	-
PO_Clad_2 25_SM_366#2-Arg95-Clr/PVB0 015/Clr_25	1.65	0.29	0.18	0.41	58	3.45	14	-	-,-,-,S
PO_Clad_2 25_SM_366#2-Arg95-Clr/PVB0 015/Clr_25_SDL WSB 3/8"	1.65	0.29	0.16	0.37	58	3.45	13	-	-,-,-,S
PO_Clad_2 25_SM_366#2-Arg95-Clr/PVB0 015/Clr_SDL WSB 1/4"	1.65	0.29	0.16	0.37	58	3.45	13	-	-,-,-,S
PO_Clad_2 25_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5	1.48	0.26	0.45	0.45	64	3.79	33	-	-
PO_Clad_2 25_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5_SDL WSB 1/4"	1.53	0.27	0.41	0.41	64	3.70	30	-	-
PO_Clad_2 25_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5_SDL WSB 3/8"	1.59	0.28	0.41	0.41	64	3.61	29	-	-
PO_Clad_2 25_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5	1.36	0.24	0.42	0.42	67	4.23	34	Oui	-
PO_Clad_2 25_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5_SDL WSB 1/4"	1.36	0.24	0.38	0.38	67	4.12	32	-	-,NC,-,-
PO_Clad_2 25_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5_SDL WSB 3/8"	1.42	0.25	0.38	0.38	67	4.00	31	-	-,NC,-,-
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI	1.42	0.25	0.25	0.42	65	3.98	23	-	-
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI_SDL WSB 1/4"	1.48	0.26	0.23	0.38	65	3.89	21	-	-,-,SC,S
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI_SDL WSB 3/8"	1.48	0.26	0.23	0.38	65	3.78	21	-	-,-,SC,S
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI-Arg95-272#5	1.25	0.22	0.23	0.37	70	4.62	26	-	N,NC,-,-
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI-Arg95-272#5_SDL WSB 1/4"	1.25	0.22	0.21	0.33	70	4.47	25	-	-,NC,SC,S
PO_Clad_2 25_SM_272#2-Arg95-ClrCGI-Arg95-272#5_SDL WSB 3/8"	1.31	0.23	0.21	0.33	70	4.33	23	-	-,NC,SC,S
PO_Clad_2 25_SM_272#2-Arg95-272#4-Arg95-i89#6	1.14	0.20	0.21	0.36	58	4.92	27	Oui	N,NC,SC,S
PO_Clad_2 25_SM_272#2-Arg95-272#4-Arg95-i89#6_SDL WSB 1/4"	1.25	0.22	0.19	0.32	58	4.65	23	-	N,NC,SC,S
PO_Clad_2 25_SM_272#2-Arg95-272#4-Arg95-i89#6_SDL WSB 3/8"	1.25	0.22	0.19	0.32	58	4.51	23	-	-,NC,SC,S
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI	1.42	0.25	0.17	0.38	65	4.04	19	-	-,NC,SC,S
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI_SDL WSB 1/4"	1.42	0.25	0.15	0.34	65	3.93	17	-	-,-,SC,S
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI_SDL WSB 3/8"	1.48	0.26	0.15	0.34	65	3.82	16	-	-,-,SC,S
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI-Arg95-366#5	1.19	0.21	0.16	0.30	70	4.71	23	Oui	-,NC,SC,S
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI-Arg95-366#5_SDL WSB 1/4"	1.25	0.22	0.15	0.27	70	4.54	21	-	-,NC,SC,S
PO_Clad_2 25_SM_366#2-Arg95-ClrCGI-Arg95-366#5_SDL WSB 3/8"	1.31	0.23	0.15	0.27	70	4.40	20	-	-,NC,SC,S

Cl : Vitre clair / Clear glass
LOF : Low-E Energy Adv.

* Depending on the options chosen, this product can meet Energy Star specifications for your area



Notes :

Product Values are determined using the National Fenestration Rating Council (NFRC) Procedures for determining fenestration product values. Values are subject to update and can vary depending on the options chosen.

U-Factor : (btu/h*ft²F) The lower the U-Factor, the greater the resistance to heat flow and the better the insulating value will be.

SHGC : Solar Heat Gain Coefficient, the lower a window's SHGC, the less solar heat it transmits, and the greater its shading ability.

Visible Transmittance (VT) : Percentage of visible light transmitted.

R-Value : (1/U-Value) A higher R-Value increase the resistance to heat flow, result in a better insulating value.

ER : Energy Rating, this value is calculated with the U-Factor, SHGC and air infiltration of the product. The higher the ER, the better the product will be for the Northern zones and the lower the ER, the better the product will be for Southern zones.