

CLAD WOOD MULTISLIDE DOOR - 2 1/4" PANEL - Stiles and Top Rail 5", Bottom Rail 9"



ENERGY DATA

I.G.	U Factor (w/m ² *K)	U Factor (Bth/h*ft ² *°)	SHGC	VT	CR	R Value	ER	Energy Star Canada V5 - 2020	Energy Star USA V7 - 2023
Wood 5in_SM_ClrPNA-Arg95-LOF#3	1.76	0.31	0.46	0.46	52	3.27	28	-	-
Wood 5in_SM_ClrPNA-Arg95-LOF#3 SDL WSB 1/4"	1.76	0.31	0.40	0.40	52	3.27	24	-	-
Wood 5in_SM_ClrPNA-Arg95-LOF#3 SDL WSB 3/8"	1.82	0.32	0.40	0.40	52	3.11	23	-	-
Wood 5in_SM_LOF#2-Arg95-i89#4	1.53	0.27	0.40	0.45	42	3.77	29	-	-
Wood 5in_SM_LOF#2-Arg95-i89#4 SDL WSB 1/4"	1.59	0.28	0.35	0.39	42	3.57	25	-	-
Wood 5in_SM_LOF#2-Arg95-i89#4 SDL WSB 3/8"	1.65	0.29	0.35	0.39	42	3.42	24	-	-
Wood 5in_SM_272#2-Arg95-ClrCGI	1.59	0.28	0.25	0.43	54	3.57	19	-	-
Wood 5in_SM_272#2-Arg95-ClrCGI SDL WSB 1/4"	1.59	0.28	0.22	0.37	54	3.57	18	-	SC,S
Wood 5in_SM_272#2-Arg95-ClrCGI SDL WSB 0 375	1.70	0.30	0.22	0.37	54	3.35	15	-	-
Wood 5in_SM_272#2-Arg95-i89#4	1.42	0.25	0.25	0.42	44	4.03	23	-	N,NC
Wood 5in_SM_272#2-Arg95-i89#4 SDL WSB 1/4"	1.48	0.26	0.22	0.36	44	3.85	20	-	SC,S
Wood 5in_SM_272#2-Arg95-i89#4 SDL WSB 3/8"	1.59	0.28	0.22	0.36	44	3.63	18	-	SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI	1.53	0.27	0.17	0.39	55	3.64	16	-	SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI SDL WSB 1/4"	1.53	0.27	0.15	0.33	55	3.64	15	-	SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI SDL WSB 3/8"	1.65	0.29	0.15	0.33	55	3.41	12	-	-
Wood 5in_SM_366#2-Arg95-i89#4	1.36	0.24	0.17	0.38	45	4.09	20	-	N,NC,SC,S
Wood 5in_SM_366#2-Arg95-i89#4 SDL WSB 1/4"	1.48	0.26	0.15	0.32	45	3.91	16	-	N,NC,SC,S
Wood 5in_SM_366#2-Arg95-i89#4 SDL WSB 3/8"	1.53	0.27	0.15	0.32	45	3.68	15	-	SC,S
Wood 5in_SM_CG70#2-Arg95-ClrGIG	1.59	0.28	0.22	0.41	54	3.62	18	-	SC,S
Wood 5in_SM_CG70#2-Arg95-ClrGIG SDL WSB 1/4"	1.59	0.28	0.19	0.35	54	3.62	16	-	SC,S
Wood 5in_SM_CG70#2-Arg95-ClrGIG SDL WSB 3/8"	1.65	0.29	0.19	0.35	54	3.40	15	-	-
Wood 5in_SM_CG70#2-Arg95-IS20#4	1.42	0.25	0.21	0.40	45	4.02	21	-	N,NC,SC,S
Wood 5in_SM_CG70#2-Arg95-IS20#4 SDL WSB 1/4"	1.48	0.26	0.18	0.34	45	3.86	18	-	N,NC,SC,S
Wood 5in_SM_CG70#2-Arg95-IS20#4 SDL WSB 3/8"	1.53	0.27	0.18	0.34	45	3.64	17	-	SC,S
Wood 5in_SM_Clr/PVB0 015/Clr-Arg95-LOF#3	1.76	0.31	0.41	0.45	54	3.27	25	-	-
Wood 5in_SM_Clr/PVB0 015/Clr-Arg95-LOF#3 SDL WSB 1/4"	1.76	0.31	0.35	0.39	54	3.27	21	-	-
Wood 5in_SM_Clr/PVB0 015/Clr-Arg95-LOF#3 SDL WSB 3/8"	1.76	0.31	0.35	0.39	54	3.27	21	-	-
Wood 5in_SM_272#2-Arg95-Clr/PVB0 015/Clr	1.59	0.28	0.25	0.42	56	3.56	19	-	-
Wood 5in_SM_272#2-Arg95-Clr/PVB0 015/Clr SDL WSB 1/4"	1.59	0.28	0.22	0.36	56	3.56	18	-	-
Wood 5in_SM_272#2-Arg95-Clr/PVB0 015/Clr SDL WSB 3/8"	1.59	0.28	0.22	0.36	56	3.56	18	-	-

Wood 5in_SM_366#2-Arg95-Clr/PVB0 015/Clr	1.59	0.28	0.17	0.38	56	3.63	15	-	SC,S
Wood 5in_SM_366#2-Arg95-Clr/PVB0 015/Clr_SDL WSB 1/4"	1.59	0.28	0.15	0.33	56	3.63	14	-	SC,S
Wood 5in_SM_366#2-Arg95-Clr/PVB0 015/Clr_SDL WSB 3/8"	1.59	0.28	0.15	0.33	56	3.63	14	-	SC,S
Wood 5in_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5	1.42	0.25	0.42	0.42	61	3.93	33	-	-
Wood 5in_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5_SDL WSB 1/4"	1.48	0.26	0.36	0.36	61	3.80	28	-	-
Wood 5in_SM_ClrPNA-Arg95-ClrPNA-Arg95-LOF#5_SDL WSB 3/8"	1.53	0.27	0.36	0.36	61	3.67	27	-	-
Wood 5in_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5	1.31	0.23	0.40	0.40	64	4.38	34	Oui	N,NC
Wood 5in_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5_SDL WSB 1/4"	1.36	0.24	0.34	0.34	64	4.22	30	-	N,NC
Wood 5in_SM_ClrPNA-Arg95-LOF#3-Arg95-LOF#5_SDL WSB 3/8"	1.42	0.25	0.34	0.34	64	4.06	28	-	N,NC
Wood 5in_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI	1.36	0.24	0.24	0.39	62	4.14	24	-	N,NC
Wood 5in_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI_SDL WSB 1/4"	1.42	0.25	0.21	0.34	62	4.00	21	-	N,NC,SC,S
Wood 5in_SM_272#2-Arg95-ClrCGI-Arg95-ClrCGI_SDL WSB 3/8"	1.48	0.26	0.21	0.34	62	3.85	20	-	N,NC,SC,S
Wood 5in_SM_272#2-Arg95-ClrCGI-Arg95-272#5	1.19	0.21	0.22	0.34	66	4.78	26	Oui	N,NC,SC,S
Wood 5in_SM_272#2-Arg95-ClrCGI-Arg95-272#5_SDL WSB 1/4"	1.25	0.22	0.19	0.29	66	4.56	23	-	N,NC,SC,S
Wood 5in_SM_272#2-Arg95-ClrCGI-Arg95-272#5_SDL WSB 3/8"	1.31	0.23	0.19	0.29	66	4.36	22	-	N,NC,SC,S
Wood 5in_SM_272#2-Arg95-272#4-Arg95-i89#6	1.14	0.20	0.20	0.34	56	5.06	26	Oui	N,NC,SC,S
Wood 5in_SM_272#2-Arg95-272#4-Arg95-i89#6_SDL WSB 1/4"	1.19	0.21	0.17	0.29	56	4.68	24	Oui	N,NC,SC,S
Wood 5in_SM_272#2-Arg95-272#4-Arg95-i89#6_SDL WSB 3/8"	1.25	0.22	0.17	0.29	56	4.50	22	-	N,NC,SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI	1.36	0.24	0.16	0.35	63	4.19	19	-	N,NC,SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI_SDL WSB 1/4"	1.42	0.25	0.14	0.30	63	4.04	17	-	N,NC,SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI-Arg95-ClrCGI_SDL WSB 3/8"	1.48	0.26	0.14	0.30	63	3.89	15	-	N,NC,SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI-Arg95-366#5	1.19	0.21	0.15	0.28	66	4.86	22	Oui	N,NC,SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI-Arg95-366#5_SDL WSB 1/4"	1.25	0.22	0.13	0.24	66	4.63	20	-	N,NC,SC,S
Wood 5in_SM_366#2-Arg95-ClrCGI-Arg95-366#5_SDL WSB 3/8"	1.31	0.23	0.13	0.24	66	4.43	19	-	N,NC,SC,S
Wood 5in_SM_Clr/PVB0.015/272-Arg95-ClrCGI-19mm	1.70	0.30	0.25	0.42	51	3.36	17	-	-
Wood 5in_SM_Clr/PVB0.015/272-Arg95-ClrCGI-19mm_SDL WSB 1/4"	1.87	0.33	0.22	0.36	51	3.07	12	-	-
Wood 5in_SM_Clr/PVB0.015/272-Arg95-ClrCGI-19mm_SDL WSB 3/8"	2.16	0.38	0.22	0.36	43	2.64	5	-	-
Wood 5in_SM_Clr/PVB0.015/366-Arg95-ClrCGI-19mm	1.65	0.29	0.17	0.38	51	3.41	13	-	-
Wood 5in_SM_Clr/PVB0.015/366-Arg95-ClrCGI-19mm_SDL WSB 1/4"	1.82	0.32	0.15	0.33	51	3.11	9	-	-
Wood 5in_SM_Clr/PVB0.015/366-Arg95-ClrCGI-19mm_SDL WSB 3/8"	2.10	0.37	0.15	0.33	43	2.67	2	-	-
Wood 5in_SM_Clr/PVB0.015/272-Arg95-ClrCGI-25mm	1.59	0.28	0.24	0.42	56	3.55	19	-	-
Wood 5in_SM_Clr/PVB0.015/272-Arg95-ClrCGI-25mm_SDL WSB 1/4"	1.59	0.28	0.21	0.36	56	3.55	17	-	-
Wood 5in_SM_Clr/PVB0.015/272-Arg95-ClrCGI-25mm_SDL WSB 3/8"	1.59	0.28	0.21	0.36	56	3.55	17	-	-
Wood 5in_SM_Clr/PVB0.015/366-Arg95-ClrCGI-25mm	1.59	0.28	0.17	0.38	56	3.62	15	-	SC,S
Wood 5in_SM_Clr/PVB0.015/366-Arg95-ClrCGI-25mm_SDL WSB 1/4"	1.59	0.28	0.15	0.33	56	3.62	14	-	SC,S
Wood 5in_SM_Clr/PVB0.015/366-Arg95-ClrCGI-25mm_SDL WSB 3/8"	1.59	0.28	0.15	0.33	56	3.62	14	-	SC,S

CI : Vitre clair / Clear glass

LOF : Low-E Energy Adv.

* Depending on the options chosen, this product can meet Energy Star specifications for your area

Notes :

Product Values are determined using the National Fenestration Rating Council (NFRC) Procedures for determining fenestration product values. Values are subject to update and can vary depending on the options chosen.

U-Factor : (btu/h*ft²F) The lower the U-Factor, the greater the resistance to heat flow and the better the insulating value will be.

SHGC : Solar Heat Gain Coefficient, the lower a window's SHGC, the less solar heat it transmits, and the greater its shading ability.

Visible Transmittance (VT) : Percentage of visible light transmitted.

R-Value : (1/U-Value) A higher R-Value increase the resistance to heat flow, result in a better insulating value.

ER : Energy Rating, this value is calculated with the U-Factor, SHGC and air infiltration of the product. The higher the ER, the better the product will be for the Northern zones and the lower the ER, the better the product will be for Southern zones.

